

Appln No. 09/919,365

Amdt date March 9, 2005

Reply to Office action of December 16, 2004

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1. (Currently Amended) A method for allocating bandwidth within a network domain by a network server operably coupled to a network domain edge node, comprising:

providing a database operably coupled to the network server, the database including path-level data comprising Quality of Service (QoS) information for paths within the network domain and link-level data for linksa~~path~~ within the network domain;

receiving by the network server from the network domain edge node a flow request for a requested~~the~~ path; and

satisfying by the network server the flow request using the link-level data if the network server determines the network server cannot satisfy the flow request using the path-level data.

Claim 2. (Currently Amended) The method of claim 1, wherein the path-level data includes for each path unused bandwidth allocated to the path and a path state, the method further comprising satisfying by the network server the flow request using the unused bandwidth if the requested path is not in a critical state and the requested path has enough unused bandwidth to satisfy the flow request.

Appln No. 09/919,365

Amdt date March 9, 2005

Reply to Office action of December 16, 2004

Claim 3. (Currently Amended) The method of claim 2, wherein the link-level data ~~further~~ includes for each link quotas of bandwidth available to the[[a]] link, the method further comprising allocating by the network server to each link along the requested path a quota of bandwidth from the quotas of bandwidth available to the link if the requested path does not have enough unused bandwidth to satisfy the flow request.

Claim 4. (Currently Amended) The method of claim 3, wherein the link-level data further includes for each link a link state and the path-level data further includes for each path a set of critical links along the path, the method further comprising allocating by the network server bandwidth to each link in the set of critical links from unused bandwidth reclaimed from another path on each link.

Claim 5. (Currently Amended) A method for allocating bandwidth within a network domain by a distributed network server, the distributed network server including a central network server and a plurality of edge network servers, comprising:

providing a plurality of path-level databases operably coupled to the plurality of edge network servers, the path-level databases including path-level data comprising Quality of Service (QoS) state information for paths within the network domain;

Appln No. 09/919,365

Amdt date March 9, 2005

Reply to Office action of December 16, 2004

providing a link-level database operably coupled to the central network server, the link-level database including link-level data for links ~~in~~along the paths within the network domain;

receiving by the distributed network server from a network domain edge node operably coupled to an edge network server a flow request for a path within the network domain; and

satisfying by the distributed network server the flow request using the link-level data if the network server determines the distributed network server cannot satisfy the flow request using the path-level data.

Claim 6. (Original) The method of claim 5, wherein the path-level data includes unused bandwidth allocated to the path and a path state, the method further comprising satisfying by the edge network server the flow request using the unused bandwidth if the path is not in a critical state and the unused bandwidth is sufficient to satisfy the flow request.

Claim 7. (Original) The method of claim 6, wherein the link-level data further includes quotas of bandwidth available to a link, the method further comprising allocating by the central network server to each link along the path a quota of bandwidth from the quotas of bandwidth available to the link if the path does not have enough unused bandwidth to satisfy the flow request.

**Appln No. 09/919,365**

**Amdt date March 9, 2005**

**Reply to Office action of December 16, 2004**

Claim 8. (Original) The method of claim 7, wherein the link-level data further includes a link state and the path-level data further includes a set of critical links along the path, the method further comprising allocating by the central network server bandwidth to each link in the set of critical links from unused bandwidth reclaimed from another path on each link.

Claim 9. (Original) The method of claim 7, the method further comprising rejecting by the edge network server the flow request if a link along the path does not have a quota of bandwidth available to the link for satisfying the flow request

Claim 10. (Currently Amended) A data processing system adapted to allocate bandwidth within a network domain, comprising:

- a database including path-level data comprising Quality of Service (QoS) information and link-level data for a path within the network domain;

- a processor; and

- a memory operably coupled to the processor and having program instructions stored therein, the processor being operable to execute the program instructions, the program instructions including:

- receiving from a network domain edge node a flow request for the path; and

- satisfying the flow request using the link-level data if the flow request cannot be satisfied using the path-level data.

**Appln No. 09/919,365**

**Amdt date March 9, 2005**

**Reply to Office action of December 16, 2004**

Claim 11. (Original) The data processing system of claim 10, wherein the path-level data includes unused bandwidth allocated to the path and a path state, the program instructions further including satisfying the flow request using the unused bandwidth if the path is not in a critical state and the path has enough available unused bandwidth to satisfy the flow request.

Claim 12. (Original) The data processing system of claim 11, wherein the link-level data further includes quotas of bandwidth available to a link, the program instructions further including allocating to each link along the path a quota of bandwidth from the quotas of bandwidth available to the link if the path does not have enough unused bandwidth to satisfy the flow request.

Claim 13. (Original) The data processing system of claim 12, wherein the link-level data further includes a link state and the path-level data further includes a set of critical links along the path, the program instructions further including allocating bandwidth to each link in the set of critical links from unused bandwidth reclaimed from another path on each link.

Claim 14. (Currently Amended) A computer readable media embodying program instructions for execution by a computer, the program instructions adapting a computer to allocate bandwidth within a network domain, program instructions comprising:

Appln No. 09/919,365

Amdt date March 9, 2005

Reply to Office action of December 16, 2004

accessing a database including path-level data comprising path Quality of Service (QoS) information and link-level data comprising link Quality of Service (QoS) information for a path within the network domain;

receiving from a network domain edge node a flow request for a path; and

satisfying the flow request using the link-level data if the flow request cannot be satisfied using the path-level data.

Claim 15. (Original) The computer readable medium of claim 14, wherein the path-level data includes unused bandwidth allocated to the path and a path state, the program instructions further comprising satisfying the flow request using the unused bandwidth if the path is not in a critical state and the path has enough unused bandwidth to satisfy the flow request.

Claim 16. (Original) The computer readable medium of claim 15, wherein the link-level data further includes quotas of bandwidth available to a link, the program instructions further comprising allocating to each link along the path a quota of bandwidth from the quotas of bandwidth available to the link if the path does not have enough unused bandwidth to satisfy the flow request.

Claim 17. (Original) The computer readable medium of claim 16, wherein the link-level data further includes a link state and the path-level data further includes a set of critical links

**Appln No. 09/919,365**

**Amdt date March 9, 2005**

**Reply to Office action of December 16, 2004**

along the path, the program instructions further comprising allocating bandwidth to each link in the set of critical links from unused bandwidth reclaimed from another path on each link.

Claim 18. (Original) A method for allocating bandwidth within a network domain by a bandwidth broker operably coupled to a network domain edge node, comprising:

providing a network QoS state database operably coupled to the bandwidth broker, the network QoS state database including:

path-level data for a path within the network domain, including:

unused bandwidth allocated to the path;  
a set of critical links along the path; and  
a path state; and

link-level data for links along the path, including:

quotas of bandwidth available to a link; and  
a link state;

receiving by the bandwidth broker from the network domain edge node a flow request for the path;

satisfying by the network server the flow request using the unused bandwidth if the path is not in a critical state and the path has enough unused bandwidth to satisfy the flow request;

allocating by the network server to each link along the path a quota of bandwidth from the quotas of bandwidth available to the link if the path is not in a critical state and

**Appln No. 09/919,365**

**Amdt date March 9, 2005**

**Reply to Office action of December 16, 2004**

the path does not have enough unused bandwidth to satisfy the flow request; and

allocating by the network server bandwidth to each link in the set of critical links from unused bandwidth reclaimed from a another path on each link if the path is in a critical state.